```
;;;
```

```
        },
        {styp ? uopr != OPR_DRF) ?
        {
            read_token()
            d = loadarg4(0)
            token != CLOSE_PARENTHESIS ? done = 1,
            {
                read_token()

                styp == 1 ?
                {
                    sadr >= 0xFF80 || sadr < 0x80 ?
                    {
                        writecode("\x8D\x5E", 2)
                        writecode(#sadr, 1)
                    },
                    {
                        writecode("\x8D\x9E", 2)
                        writecode(#sadr, 2)
                    }
                    ; 0100 8D5E01         LEA
BX,[BP+01]
                    ; 0103 8D9E8000       LEA
BX,[BP+0080]

                    writecode("\xFF\xD3", 2)
                    ; 0106 FFD3           CALL    BX
                },
                styp == 2 ?
                {
                    sadr = sadr - (address + 3)
                    writecode("\xE8", 1)
                    writecode(#sadr, 2)
                    ; 0100 E80000         CALL    0103
                },
                styp == 3 ? ; heap
                {
                    sadr = sadr - 1
                    sadr >= 0xFF80 || sadr < 0x80 ?
                    {
                        writecode("\x8D\x5D", 2)
                        writecode(#sadr, 1)
                    },
                    {
                        writecode("\x8D\x9D", 2)
                        writecode(#sadr, 2)
                    }
                    ; 0100 8D5D01         LEA
BX,[DI+01]
                    ; 0103 8D9D8000       LEA
BX,[DI+0080]

                    writecode("\xFF\xD3", 2)
                    ; 0106 FFD3           CALL    BX
                }
            },
            {
                uopr != OPR_DRF ?
                {
                    error(8)
                    done = 1
                },
                {
                    loadvar(styp, sadr)

                    writecode("\x89\xC3", 2)

                    read_token()
                    loadargs(1)
                    token != CLOSE_PARENTHESIS ? done = 1,
                    {
                        read_token()
                        writecode("\xFF\xD3", 2)
                        ; 0100 89C3           MOV     BX,AX
                        ; 0102 FFD3           CALL    BX
                    }
                    uopr = 0
                }
            }
            done == 0 ? fixstack(d)
        },
        token == OPEN_BRACKET ?
        {
            read_token()
            styp == 0 ? writecode("\x50", 1)
            ; 0101 50             PUSH    AX

            @primary_expression() == 0 ? done = 1,
            token != CLOSE_BRACKET ? done = 1,
            {
                read_token()
                writecode("\xD1\xE0", 2)
                ; 0100 D1E0           SHL     AX,1
                styp ?
                {
                    writecode("\x89\xC3", 2)
                    ; 0100 89C3           MOV     BX,AX

                    token == BINARY_OPERATOR && operator ==
OPR_SET &&
                          uopr != OPR_DRF ?
                    {
                        loadadr(styp, sadr)
                        writecode("\x01\xD8", 2)
                        ; 0102 01D8           ADD     AX,BX
                    },
                    uopr == OPR_DRF ?
                    {
                        loadvar(styp, sadr)

                        token == BINARY_OPERATOR &&
operator == OPR_SET ?
                            writecode("\x01\xD8", 2),
                            ; 0102 01D8           ADD
AX,BX
                            writecode("\x01\xC3\x8B\x07",
4)
                            ; 0102 01C3           ADD
BX,AX
                            ; 0104 8B07           MOV
AX,[BX]

                        uopr = 0
                    },
                    {
                        loadadr(styp, sadr)
                        writecode("\x01\xC3\x8B\x07", 4)
                        ; 0102 01C3           ADD     BX,AX
                        ; 0104 8B07           MOV
AX,[BX]
                    }
                },
                {
                    uopr != OPR_DRF ?
                    {
                        error(9)
                        done = 1
                    },
                    {
                        writecode("\x5B\x01\xC3\x8B\x07", 5)
                        ; 0100 5B             POP     BX
                        ; 0101 01C3           ADD     BX,AX
                        ; 0103 8B07           MOV     AX,[BX]
                    }
                }
            },
            token == BINARY_OPERATOR && operator == OPR_SET ?
            {
                uopr == OPR_DRF ?
                {
                    styp ? loadvar(styp, sadr)
                    uopr = 0
                },
                {
                    styp == 0 ?
                    {
                        error(10)
                        done = 1
                    }
                    styp == -1 ?
                    {
                        ; Special processing
                        read_token()
                        @primary_expression() ?
writecode("\xFF\xE0", 2), done = 1
                        ; 0100 FFE0           JMP     AX
                    }, loadadr(styp, sadr)
                }
            },
            styp ?
            {
                uopr == OPR_ADR ?
                {
                    uopr = 0
                    loadadr(styp, sadr)
                }, loadvar(styp, sadr)
            }

            done == 0 ? uopr == OPR_ADR ? done = 1,
            uopr == OPR_DRF ?
            {
                writecode("\x89\xC3\x8B\x07", 4)
                ; 0100 89C3           MOV     BX,AX
                ; 0102 8B07           MOV     AX,[BX]
            },
            uopr == OPR_SUB ?
            {
                writecode("\xF7\xD8", 2)
                ; 0100 F7D8           NEG     AX
            },
            uopr == OPR_NOT ?
            {
                writecode("\xF7\xD0", 2)
                ; 0100 F7D0           NOT     AX
            },
            uopr == OPR_LNO ?
            {
                writecode("\x09\xC0\x74\x03\xB8\x01\x00\x48", 8)
                ; 0100 09C0           OR      AX,AX
                ; 0102 7403           JZ      0107
                ; 0104 B80100         MOV     AX,0001
                ; 0107 48             DEC     AX
            }

            done - 1
        }
        execute(operator) :=
        {
            operator == OPR_AND ?
            {
                writecode("\x5B\x21\xD8", 3)
                ; 0100 5B             POP     BX
                ; 0101 21D8           AND     AX,BX
            },
            operator == OPR_LND ?
            {

                writecode("\x5B\x09\xDB\x75\x02\x31\xC0\x09\xC0", 9)
                    ; 0100 5B             POP     BX
                    ; 0101 09DB           OR      BX,BX
                    ; 0103 7502           JNZ     0107
                    ; 0105 31C0           XOR     AX,AX
                    ; 0107 09C0           OR      AX,AX
                },
                operator == OPR_MUL ?
                {
                    writecode("\x5B\xF7\xE3", 3)
                    ; 0100 5B             POP     BX
                    ; 0101 F7E3           MUL     BX
                },
                operator == OPR_DIV ?
                {
                    writecode("\x89\xC3\xBA\x00\x00\x58\xF7\xF3", 8)
                    ; 0100 89C3           MOV     BX,AX
                    ; 0102 BA0000         MOV     DX,0000
                    ; 0105 58             POP     AX
                    ; 0106 F7F3           DIV     BX
                },
                operator == OPR_OR || operator == OPR_LOR ?
                {
                    writecode("\x5B\x09\xDB", 3)
                    ; 0100 5B             POP     BX
                    ; 0101 09DB           OR      AX,BX
                },
                operator == OPR_ADD ?
                {
                    writecode("\x5B\x01\xDB", 3)
                    ; 0100 5B             POP     BX
                    ; 0101 01DB           ADD     AX,BX
                },
                operator == OPR_SUB ?
                {
                    writecode("\x89\xC3\x58\x29\xD8", 5)
                    ; 0100 89C3           MOV     BX,AX
                    ; 0102 58             POP     AX
                    ; 0103 29D8           SUB     AX,BX
                },
                operator == OPR_LT ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x72\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7202           JB      010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_GT ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x77\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7702           JA      010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_LTE ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x76\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7602           JBE     010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_GTE ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x73\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7302           JNB     010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_EQU ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x74\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7402           JZ      010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_NEQ ?
                {

                writecode("\x5B\x39\xC3\xB8\x01\x00\x75\x02\x31\xC0"
, 10)
                    ; 0100 5B             POP     BX
                    ; 0101 39C3           CMP     BX,AX
                    ; 0103 B80100         MOV     AX,0001
                    ; 0106 7502           JNZ     010A
                    ; 0108 31C0           XOR     AX,AX
                },
                operator == OPR_SET ?
                {
                    ; In unary-expression(), we can always tell if
the next
                    ; unevaluated token is an OPR_SET operator. If
it is, we
                    ; can check if the current expression is an
lvalue, and
                    ; store the address instead of dereferencing.
                    ; The NOP ensures fixed-length code that
                    ; is required for $ to work.
                    writecode("\x5B\x89\x07\x90", 4)
                    ; 0100 5B             POP     BX
                    ; 0101 8907           MOV     [BX],AX
                    ; 0103 90             NOP
                },
                operator == OPR_SHL ?
                {
                    writecode("\x89\xC1\x58\xD3\xE0", 5)
                    ; 0100 89C1           MOV     CX,AX
                    ; 0102 58             POP     AX
                    ; 0103 D3E0           SHL     AX,CL
                },
                operator == OPR_SHR ?
                {
                    writecode("\x89\xC1\x58\xD3\xE8", 5)
                    ; 0100 89C1           MOV     CX,AX
                    ; 0102 58             POP     AX
                    ; 0103 D3E8           SHR     AX,CL
                },
                operator == OPR_MOD ?
                {

                writecode("\x89\xC3\xBA\x00\x00\x58\xF7\xF3\x89\xD0"
, 10)
                    ; 0100 89C3           MOV     BX,AX
                    ; 0102 BA0000         MOV     DX,0000
                    ; 0105 58             POP     AX
                    ; 0106 F7F3           DIV     BX
                    ; 0108 89D0           MOV     AX,DX
                },
                {
                    error(17)
                    writecode("\x83\xC4\x02", 3)
                    ; 0100 83C402         ADD     SP,+02
                }
            }

            simple_expression() :=
            {
                stkopr[7] := ?       ; Seven precedence levels
                stack := 0
                found := 0
                rval := 1

                token == NUMBER && number == 0 ?
                {
                    pos[3] := ?
                    read_position(#pos)
                    read_token()

                    token == BINARY_OPERATOR && operator == OPR_NEQ
? read_token(), set_position(#pos)
                    }

                    unary_expression() ?
                    {
                        p := $
                        token == OPERATOR || token == BINARY_OPERATOR ?
                        {
                            {
                                q := $
                                0 != (stack > 0 ? precedence(operator)
<= precedence(stkopr[stack - 1])) ?
                                {
                                    stack = stack - 1
                                    execute( stkopr[stack])
                                    $ = q
                                }
                            }
                            writecode("\x50", 1)
                            ; 0100 50             PUSH    AX
                            stkopr[stack] = operator
                            stack = stack + 1
                            read_token()
                            unary_expression() ? $ = p,  rval = 0
                        }
                        p = $
                        stack > 0 ?
                        {
                            stack = stack - 1
                            execute( stkopr[stack])
                            $ = p
                        }
                        rval
                    }, 0
            }
            evaluate(value, operator) :=
            {
                rval := 1

                operator == OPR_AND ? number = value & number,
                operator == OPR_MUL ? number = value * number,
                operator == OPR_DIV ? number = value / number,
                operator == OPR_OR ? number = value | number,
                operator == OPR_ADD ? number = value + number,
                operator == OPR_SUB ? number = value - number,
                operator == OPR_LT ? number = value < number,
                operator == OPR_GT ? number = value > number,
                operator == OPR_LTE ? number = value <= number,
                operator == OPR_GTE ? number = value >= number,
                operator == OPR_EQU ? number = value == number,
                operator == OPR_NEQ ? number = value != number,
                operator == OPR_LND ? number = value && number,
                operator == OPR_LOR ? number = value || number,
                operator == OPR_NOT ? number = ~number,
                operator == OPR_LNO ? number = !number,
                operator == OPR_SHL ? number = value << number,
                operator == OPR_SHR ? number = value >> number,
                operator == OPR_MOD ? number = value % number,
                {
                    error(11)
                    rval = 0
                }
                rval
            }
            constant_expression() :=
            {
                stkval[7] := ?       ; Seven precedence levels
                stkopr[7] := ?
                stack := 0
                rval := 1

                token == OPERATOR || token == UNARY_OPERATOR ?
                {
                    operator == OPR_ADR || operator == OPR_DRF ?
rval = 0,
                    stack > 5 ?
                    {
                        error(12)
                        rval = 0
                    },
                    {
                        stkopr[stack] = operator
                        stkval[stack] = 0
                        stack = stack + 1
                        read_token()
                    }
                }

                p := $
                rval ?
                {
                    token == OPEN_PARENTHESIS ?
                    {
                        read_token()
                        constant_expression() ?
                        {
                            token == CLOSE_PARENTHESIS ?
read_token(), rval = 0
                        }, rval = 0
                    },
                    token == NUMBER || token == CHARACTER ?
read_token(), rval = 0

                    rval && ((token == OPERATOR) || (token ==
BINARY_OPERATOR)) ?
                    {
                        operator == OPR_SET ? rval = 0,
                        {
                            p := $

                            stack > 0 && precedence(operator) <=
precedence(stkopr[stack - 1]) ?
                            {
                                stack = stack - 1
                                evaluate(stkval[stack],
stkopr[stack])

                                $ = p
                            }
                            stack > 5 ?
                            {
                                error(12)
                                rval = 0
                            },
                            {
                                stkopr[stack] = operator
                                stkval[stack] = number
                                stack = stack + 1
                                read_token()
                            }
                            $ = p
                        }
                    }

                    rval ?
                    {
                        p = $
                        stack > 0 ?
                        {
                            stack = stack - 1
                            evaluate(stkval[stack], stkopr[stack])
                        }
                    }
                    rval
                }
                compound_expression() :=
                {
                    token == OPEN_BRACE ?
                    {
                        read_token()
                        ; Add new namespace
                        oldbase := basespace
                        newspace(0) ?
                        {
                            p := $
                            token != CLOSE_BRACE ?
                            {
                                @primary_expression() ? $ = p
                            },
                            {
                                read_token()
                                oldbase != basespace ?
                                {
                                    namespace > 3 ?
                                    {
                                        d := oldbase - basespace
                                        d < 0x80 || d >= 0xFF80 ?
                                        {
                                            writecode("\x83\xC4", 2)
                                            writecode(#d, 1)
                                        },
                                        {
                                            writecode("\x81\xC4", 2)
                                            writecode(#d, 2);
                                        }
                                        ; 0100 83C400         ADD
SP,+00
                                        ; 0103 81C48000       ADD
SP,0080
                                    }
                                    basespace = oldbase
                                }
                                oldspace(0)
                            }
                        }, 0
                    }, 0
                }
```

```
                _primary_expression() :=
                {
                    pos[3] := ?
                    r := 0

                    read_position(#pos)

                    constant_expression() ?
                    {
                        function ?
                        {
                            ; Assignment
                            writecode("\xB8", 1)
                            writecode(#number, 2)
                            ; 0100 B80000         MOV     AX,0000
                        },
                        {
                            ; Add constant to heap
                            writeheap(#number, 2)
                        }
                        r = 1
                    },
                    {
                        set_position(#pos)
                        token == OPEN_BRACE ? r = compound_expression(),
                        {
                            read_position(#pos)
                            ; Here we have an ambiguity. If we read a
symbol, we may
                            ; have a declarator; we need to look for an
':=', or we need
                            ; to look for an '[ constant_expression ]
:=' sequence to
                            ; determine what we have here.

                            token == SYMBOL ?
                            {
                                read_token()
                                token == OPEN_BRACKET ?
                                {
                                    read_token()
                                    constant_expression() && token ==
CLOSE_BRACKET ?
                                        read_token(), token = 0
                                }
                                token == ASSIGN_OPERATOR ?
                                {
                                    set_position(#pos)
                                    r = @definition()
                                },
                                {
                                    set_position(#pos)
                                    r = simple_expression()
                                }
                            }, r = simple_expression()
                        }
                    }

                    (r ? (token == QUESTION_MARK)) ?
                    {
                        f[2] := 0, 0
                        a := ?
                        writecode("\x09\xC0\x75\x03\xE9\x00\x00", 7)
                        ; 0100 09C0           OR      AX,AX
                        ; 0102 7503           JNZ     0107
                        ; 0104 E90000         JMP     0107

                        seek(com, #f - 1)
                        f[0] < 2 ? f[1] = f[1] - 1
                        f[0] = f[0] - 2
                        a = address
                        read_token()

                        @primary_expression() ?
                        {
                            g[2] := 0, 0
                            h[2] := 0, 0

                            token == COMMA ?
                            {
                                writecode("\xE9\x00\x00", 3)
                                ; 0100 E90000         JMP     0103
                                seek(com, #h - 1)
                                h[0] < 2 ? h[1] = h[1] - 1
                                h[0] = h[0] - 2
                            }

                            seek(com, #g, 1)
                            seek(com, #f, 0)
                            a = address - a
                            write(com, #a, 2)
                            seek(com, #g, 0)
                            a = address

                            token == COMMA ?
                            {
                                read_token()
                                r = @primary_expression()
                            }

                            h[0] || h[1] ?
                            {
                                g[0] = g[1] = 0)
                                seek(com, #g, 1)
                                seek(com, #h, 0)
                                a = address - a
                                write(com, #a, 2)
                                seek(com, #g, 0)
                            }
                        }, r = 0
                    }
                    r
                }
                declarator() :=
                {
                    token == SYMBOL ?
                    {
                        read_token()
                        t := token
                        t == OPEN_PARENTHESIS ?
                        {
                            function ? error(13),
                            {
                                addname(#symbol, address)

                                ; Function preamble emitted here
                                writecode("\x55\x89\xE5", 3)
                                ; 0100 55             PUSH    BP
                                ; 0101 89E5           MOV     BP,SP

                                function = 1
                                ; start new local namespace
                                newspace(1)
                                basespace = 0
                                read_token()
                                p := $
                                token == SYMBOL ?
                                {
                                    addname(#symbol, basespace)
                                    basespace = basespace - 2
                                    read_token()
                                    token == COMMA ?
                                    {
                                        read_token()
                                        $ = p
                                    }
                                }
                                {
                                    ; Fix up newly added symbols
                                    i := 0
                                    basespace = 2 - basespace
                                    p := $
                                    i < basespace ?
                                    {
                                        space[currspace + i + 1] =
                                            space[currspace + 1 + 1] +
basespace

                                        i = i + 2
                                        $ = p
                                    }
                                }
                                basespace = 0
                                token == CLOSE_PARENTHESIS ?
                                {
                                    read_token()
                                }, error(14)
                            }
                        },
                        t == OPEN_BRACKET ?
                        {
                            read_token()
                            constant_expression() ?
                            {
                                number = number * 2
                                function ?
                                {
                                    basespace = basespace - number

                                    number < 0x80 || number >= 0xFF80 ?
                                    {
                                        number = number & 0xFF
                                        writecode("\x83\xEC", 2)
                                        writecode(#number, 1)
                                    },
                                    {
                                        writecode("\x81\xEC", 2)
                                        writecode(#number, 2)
                                    }
                                    ; 0100 83EC02         SUB     SP,+02
                                    ; 0103 81EC8000       SUB
SP,0080
                                    addname(#symbol, basespace)
                                },
                                {
                                    heapadj = heapadr + number
                                    symbol[0] = symbol[0] | 0x80
                                    addname(#symbol, heapadr + 1)
                                }
                                token == CLOSE_BRACKET ?
                                {
                                    read_token()
                                }, 0
                            }, error(15)
                        },
                        {
                            ; add symbol to current namespace
                            function ?
                            {
                                basespace = basespace - 2
                                writecode("\x83\xEC\x02", 3)
                                addname(#symbol, basespace)
                                ; 0100 83EC02         SUB     SP,+02
                            },
                            {
                                ; high bit in bit0 indicates a heap
symbol
                                symbol[0] = symbol[0] | 0x80
                                addname(#symbol, heapadr + 1)
                            }
                            1
                        }
                    }, 0
                }
                initializer() :=
                {
                    ; Whatever we do, at this point our lvalue is the
last
                    ; item in our current namespace.

                    a := space[currspace + 1]
                    rval := 1
                    p := $

                    token == QUESTION_MARK ?
                    {
                        ; We're happy. No code emitted.
                        function == 0 ? writeheap("\x00\x00", 2)
                        read_token();
                    },
                    @primary_expression() ?
                    {
                        (namespace == 2 ? function) ?
                        {
                            ; Function postamble emitted here
                            writecode("\x89\xEC\x5D\xC3", 4)
                            ; 0100 89EC           MOV     SP,BP
                            ; 0102 5D             POP     BP
                            ; 0103 C3             RET

                            function = 0
                            oldspace(1)
                        },
                        {
                            function ?
                            {
                                ; Emit assignment code for local
variable
                                ; fixed-length code needed to ensure $
works properly.
                                writecode("\x89\x86", 2)
                                writecode(#a, 2)
                                ; 010D 89868000       MOV
[BP+0080],AX
                                a = a + 2
                            }
                        }, rval = 0

                        rval ?
                        {
                            token == COMMA ?
                            {
                                read_token()
                                $ = p
                            },
                            {
                                p = $
                                heapadj > heapadr ?
                                {
                                    writeheap("\x00\x00", 2);
                                    $ = p
                                }
                                1
                            }
                        }
                    }
                }
                definition() :=
                {
                    declarator() ?
                    {
                        token == ASSIGN_OPERATOR ?
                        {
                            p := $
                            read_token()
                            initializer()
                        }, 0
                    }, 0
                }
                program() :=
                {
                    newspace(0)

                    ; Startup code
                    writecode("\x8F\x10\x01\xB8\x01\x00\x02\x1E\x00\x00\
xB8\x82\x00\x00\x88\x27\x00\xFE\x81\x75\x02\x88\xD8\x50\xE8\x
05\x00\x83\xC4\x02\xCD\x20\xC3", 32)
                    ; 0100 BF1001         MOV     DI,0110   ; Heap base
at offset 1
                    ; 0103 B88100         MOV     BX,0081   ; Command
line
                    ; 0106 021E8000       ADD     BL,[0080]
                    ; 010A B88200         MOV     AX,0082
                    ; 010D 8827           MOV     [BX],AH
                    ; 010F 80FB81         CMP     BL,81
                    ; 0112 7502           JNZ     0116
                    ; 0114 88D8           MOV     AL,BL
                    ; 0116 50             PUSH    AX      ; as function
parameter
                    ; 0117 E80500         CALL    011F  ; start address
at offset 24
                    ; 011A 83C402         ADD     SP,+02    ; must be
relative to 0x11A
                    ; 011D CD20           INT     20
                    ; 011F C3             RET

                    read_token()
                    p := $
                    token != FILE_END ?
                    {
                        @definition() ? $ = p, error(16)
                    }

                    c[2] := 1, 0
                    seek(com, #c, 0)
                    write(com, #address, 2)

                    a := findname("_\0", 1)
                    a ?
                    {
                        a = a - 0x011A
                        c[0] = 24
                        c[1] = 0
                        seek(com, #c, 0)
                        write(com, #a, 2)
                    }, error(0)
                    0
                }

                (arg) :=
                {
                    definition = #_definition
                    primary_expression = #_primary_expression

                    c[128] := ?

                    n := strlen(arg)
                    strcpy(#c, arg)

                    at(#c, n - 2) != '.' || at(#c, n - 1) & 0xDF != 'W'
? strcpy(#c + n, ".wb4"), n = n + 2

                    src = open(#c, 0),
                    strcpy(#c + n, ".COM\0");
                    com = open(#c, 1)
                    strcpy(#c + n, ".TMP\0");
                    tmp = open(#c, 1)

                    src == 0 ? puts(stderr, "Can't open source
file\r\n\0")
                    tmp == 0 ? puts(stderr, "Can't open temporary
file\r\n\0")
                    com == 0 ? puts(stderr, "Can't open output
file\r\n\0"),
                    {
                        program()
                        close(src)
                        close(tmp)
                        tmp = open(#c, 0)
                        tmp ?
                        {
                            b[512] := ?
                            n := read(tmp, #b, 512)
                            p[2] := 0, 0
                            seek(com, #p, 2)
                            p = $
                            n > 0 ?
                            {
                                write(com, #b, n)
                                n = read(tmp, #b, 512)
                                $ = p
                            }
                            close(tmp)
                        }
                        unlink(#c)
                        close(com)

                        puts(stdout, "\r\nAddress map (global
symbols)\r\n==========================\r\n\0");
                        n = space[16382]
                        n == 0 ? n = currspace
                        p := $
                        n < 16379 ?
                        {
                            s := #space + space[n + 2] << 1
                            h := @s[0] & 0x80
                            @s[0] = @s[0] & 0xFF7F

                            printf(s, (h ? "heap\0", "code\0"), space[n
+ 1] + (h ? address - 1, 0), "%x (%s) %s\r\n\0", stdout)

                            n = n + 2
                            $ = p
                        }
                    }
                }
```