```
;;;
```

```
    uopr = operator
    read_token()
}

token == NUMBER || token == CHARACTER ?
{
    writecode("\xB8", 1)
    writecode(#number, 2)
    ; 0100 B80000          MOV     AX,0000
    read_token()
},
token == STRING ?
{
    heapadr >= 0xFF80 || heapadr < 0x80 ?
    {
        writecode("\x8D\x45", 2)
        writecode(#heapadr, 1)
    },
    {
        writecode("\x8D\x85", 2)
        writecode(#heapadr, 2)
    }
    ; 0107 8D4501          LEA     AX,[DI+01]
    ; 010A 8D858000        LEA     AX,[DI+0080]

    writeheap(#string, length)
    read_token()
},
token == OPEN_PARENTHESIS ?
{
    read_token()
    @primary_expression() == 0 ? done = 1,
    token != CLOSE_PARENTHESIS ? done = 1,
    read_token()
},
token == DOLLAR ?
{
    styp = 0xFFFF
    read_token()
},
token != SYMBOL ? done = 1,
{
    styp = styp + 1
    sadr = findname(#symbol, 0)
    sadr == 0 ?
    {
        styp = styp + 1
        sadr = findname(#symbol, 1)
    }
    sadr == 0 ?
    {
        styp = styp + 1
        symbol[0] = symbol[0] | 0x80
        sadr = findname(#symbol, 1)
    }
    sadr == 0 ?
    {
        symbol[0] = symbol[0] & 0xFF7F
        error(#symbol, 6)
        done = 1
    }
    done == 0 ? read_token()
}

done == 0 ? token == OPEN_PARENTHESIS ?
{
    d := 0

    styp == 0xFFFF ? done = 2,
    uopr == OPR_ADR ?
    {
        error(7)
        done = 1
    },
    (styp ? uopr != OPR_DRF) ?
    {
        read_token()
        d = loadargs(0)
        token != CLOSE_PARENTHESIS ? done = 1,
        {
            read_token()

            styp == 1 ?
            {
                sadr >= 0xFF80 || sadr < 0x80 ?
                {
                    writecode("\x8D\x5E", 2)
                    writecode(#sadr, 1)
                },
                {
                    writecode("\x8D\x9E", 2)
                    writecode(#sadr, 2)
                }
                ; 0100 8D5E01      LEA  BX,[BP+01]
                ; 0103 8D9E8000    LEA  BX,[BP+0080]

                writecode("\xFF\xD3", 2)
                ; 0106 FFD3            CALL    BX
            },
            styp == 2 ?
            {
                sadr = sadr - (address + 3)
                writecode("\x8E", 1)
                writecode(#sadr, 2)
                ; 0100 E80000          CALL    0103
            },
            styp == 3 ? ; heap
            {
                sadr = sadr - 1
                sadr >= 0xFF80 || sadr < 0x80 ?
                {
                    writecode("\x8D\x5D", 2)
                    writecode(#sadr, 1)
                },
                {
                    writecode("\x8D\x9D", 2)
                    writecode(#sadr, 2)
                }
                ; 0100 8D5D01      LEA  BX,[DI+01]
                ; 0103 8D9D8000    LEA  BX,[DI+0080]

                writecode("\xFF\xD3", 2)
                ; 0106 FFD3            CALL    BX
            }
        }
    },
    {
        uopr != OPR_DRF ?
        {
            error(8)
            done = 1
        },
        {
            loadvar(styp, sadr)

            writecode("\x89\xC3", 2)

            read_token()
            loadargs(1)
            token != CLOSE_PARENTHESIS ? done = 1,
            {
                read_token()
                writecode("\xFF\xD3", 2)
                ; 0100 89C3            MOV     BX,AX
                ; 0102 FFD3            CALL    BX
            }
            uopr = 0
        }
    }
    done == 0 ? fixstack(d)
},
token == OPEN_BRACKET ?
{
    read_token()
    styp == 0 ? writecode("\x50", 1)
    ; 0101 50              PUSH    AX

    @primary_expression() == 0 ? done = 1,
    token != CLOSE_BRACKET ? done = 1,
    {
        read_token()
        writecode("\xD1\xE0", 2)
        ; 0100 D1E0          SHL     AX,1
        styp ?
        {
            writecode("\x89\xC3", 2)
            ; 0100 89C3            MOV     BX,AX

            token == BINARY_OPERATOR &&
            operator == OPR_SET && uopr != OPR_DRF ?
            {
                loadadr(styp, sadr)
                writecode("\x01\xD8", 2)
                ; 0102 01D8            ADD     AX,BX
            },
            uopr == OPR_DRF ?
            {
                loadvar(styp, sadr)

                token == BINARY_OPERATOR &&
                operator == OPR_SET ?
                    writecode("\x01\xD8", 2),
                    ; 0102 01D8        ADD     AX,BX
                    writecode("\x01\xC3\x8B\x07", 4)
                    ; 0102 01C3        ADD     BX,AX
                    ; 0104 8B07        MOV     AX,[BX]
                uopr = 0
            },
            {
                loadadr(styp, sadr)
                writecode("\x01\xC3\x8B\x07", 4)
                ; 0102 01C3            ADD     BX,AX
                ; 0104 8B07            MOV     AX,[BX]
            }
        },
        {
            uopr != OPR_DRF ?
            {
                error(9)
                done = 1
            },
            {
                writecode("\x5B\x01\xC3\x8B\x07", 5)
                ; 0100 5B              POP     BX
                ; 0101 01C3            ADD     BX,AX
                ; 0103 8B07            MOV     AX,[BX]
            }
        }
    },
    token == BINARY_OPERATOR && operator == OPR_SET ?
    {
        uopr == OPR_DRF ?
        {
            styp ? loadvar(styp, sadr)
            uopr = 0
        },
        {
            styp == 0 ?
            {
                error(10)
                done = 1
            },
            styp == -1 ?
            {
                ; Special processing
                read_token()
                @primary_expression() ?
                    writecode("\xFF\xE0", 2), done = 1
                ; 0100 FFE0            JMP     AX
            }, loadadr(styp, sadr)
        }
    },
    styp ?
    {
        uopr == OPR_ADR ?
        {
            uopr = 0
            loadadr(styp, sadr)
        }, loadvar(styp, sadr)
    }

    done == 0 ? uopr == OPR_ADR ? done = 1,
    uopr == OPR_DRF ?
    {
        writecode("\x89\xC3\x8B\x07", 4)
        ; 0100 89C3            MOV     BX,AX
        ; 0102 8B07            MOV     AX,[BX]
    },
    uopr == OPR_SUB ?
    {
        writecode("\xF7\xD8", 2)
        ; 0100 F7D8            NEG     AX
    },
    uopr == OPR_NOT ?
    {
        writecode("\xF7\xD0", 2)
        ; 0100 F7D0            NOT     AX
    },
    uopr == OPR_LNO ?
    {
        writecode("\x09\xC0\x74\x03\xB8\x01\x00\x48", 8)
        ; 0100 09C0            OR      AX,AX
        ; 0102 7403            JZ      0107
        ; 0104 B80100          MOV     AX,0001
        ; 0107 48              DEC     AX
    }

    done - 1
}

execute(operator) :=
{
    operator == OPR_AND ?
    {
        writecode("\x5B\x21\xD8", 3)
        ; 0100 5B              POP     BX
        ; 0101 21D8            AND     AX,BX
    },
    operator == OPR_LND ?
    {

    writecode("\x5B\x09\xDB\x75\x02\x31\xC0\x09\xC0", 9)
        ; 0100 5B              POP     BX
        ; 0101 09DB            OR      BX,BX
        ; 0103 7502            JNZ     0107
        ; 0105 31C0            XOR     AX,AX
        ; 0107 09C0            OR      AX,AX
    },
    operator == OPR_MUL ?
    {
        writecode("\x5B\xF7\xE3", 3)
        ; 0100 5B              POP     BX
        ; 0101 F7E3            MUL     BX
    },
    operator == OPR_DIV ?
    {
        writecode("\x89\xC3\xBA\x00\x00\x58\xF7\xF3", 8)
        ; 0100 89C3            MOV     BX,AX
        ; 0102 BA0000          MOV     DX,0000
        ; 0105 58              POP     AX
        ; 0106 F7F3            DIV     BX
    },
    operator == OPR_OR || operator == OPR_LOR ?
    {
        writecode("\x5B\x09\xD8", 3)
        ; 0100 5B              POP     BX
        ; 0101 09D8            OR      AX,BX
    },
    operator == OPR_ADD ?
    {
        writecode("\x5B\x01\xD8", 3)
        ; 0100 5B              POP     BX
        ; 0101 01D8            ADD     AX,BX
    },
    operator == OPR_SUB ?
    {
        writecode("\x89\xC3\x58\x29\xD8", 5)
        ; 0100 89C3            MOV     BX,AX
        ; 0102 58              POP     AX
        ; 0103 29D8            SUB     AX,BX
    },
    operator == OPR_LT ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x72\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7202            JB      010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_GT ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x77\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7702            JA      010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_LTE ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x76\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7602            JBE     010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_GTE ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x73\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7302            JNB     010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_EQU ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x74\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7402            JZ      010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_NEQ ?
    {

    writecode("\x5B\x39\xC3\xB8\x01\x00\x75\x02\x31\xC0",
                10)
        ; 0100 5B              POP     BX
        ; 0101 39C3            CMP     BX,AX
        ; 0103 B80100          MOV     AX,0001
        ; 0106 7502            JNZ     010A
        ; 0108 31C0            XOR     AX,AX
    },
    operator == OPR_SET ?
    {
        ; In unary-expression(), we can always tell if
        ; the next unevaluated token is an OPR_SET
        ; operator. If it is, we can check if the
        ; current expression is an lvalue, and store the
        ; address instead of dereferencing.
        ; The NOP ensures fixed-length code that
        ; is required for $ to work.
        writecode("\x5B\x89\x07\x90", 4)
        ; 0100 5B              POP     BX
        ; 0101 8907            MOV     [BX],AX
        ; 0103 90              NOP
    },
    operator == OPR_SHL ?
    {
        writecode("\x89\xC1\x58\xD3\xE0", 5)
        ; 0100 89C1            MOV     CX,AX
        ; 0102 58              POP     AX
        ; 0103 D3E0            SHL     AX,CL
    },
    operator == OPR_SHR ?
    {

    writecode("\x89\xC1\x58\xD3\xE8", 5)
        ; 0100 89C1            MOV     CX,AX
        ; 0102 58              POP     AX
        ; 0103 D3E8            SHR     AX,CL
    },
    operator == OPR_MOD ?
    {

    writecode("\x89\xC3\xBA\x00\x00\x58\xF7\xF3\x89\xD0",
                10)
        ; 0100 89C3            MOV     BX,AX
        ; 0102 BA0000          MOV     DX,0000
        ; 0105 58              POP     AX
        ; 0106 F7F3            DIV     BX
        ; 0108 89D0            MOV     AX,DX
    },
    {
        error(17)
        writecode("\x83\xC4\x02", 3)
        ; 0100 83C402          ADD     SP,+02
    }
}

simple_expression() :=
{
    stkopr[7] := ?        ; Seven precedence levels
    stack := 0
    found := 0
    rval := 1

    token == NUMBER && number == 0 ?
    {
        pos[3] := ?
        read_position(#pos)
        read_token()
        token == BINARY_OPERATOR && operator == OPR_NEQ ?
                read_token(), set_position(#pos)
    }

    unary_expression() ?
    {
        p := $
        token == OPERATOR || token == BINARY_OPERATOR ?
        {
            {
                q := $
                0 != (stack > 0 ?
                    precedence(operator) <=
                        precedence(stkopr[stack - 1])) ?
                {
                    stack = stack - 1
                    execute(stkopr[stack])
                    $ = q
                }
            }
            writecode("\x50", 1)
            ; 0100 50              PUSH    AX
            stkopr[stack] = operator
            stack = stack + 1
            read_token()
            unary_expression() ? $ = p, rval = 0
        }
        p = $
        stack > 0 ?
        {
            stack = stack - 1
            execute(stkopr[stack])
            $ = p
        }
        rval
    }, 0
}

evaluate(value, operator) :=
{
    rval := 1

    operator == OPR_AND ? number = value & number,
    operator == OPR_MUL ? number = value * number,
    operator == OPR_DIV ? number = value / number,
    operator == OPR_OR ? number = value | number,
    operator == OPR_ADD ? number = value + number,
    operator == OPR_SUB ? number = value - number,
    operator == OPR_LT ? number = value < number,
    operator == OPR_GT ? number = value > number,
    operator == OPR_LTE ? number = value <= number,
    operator == OPR_GTE ? number = value >= number,
    operator == OPR_EQU ? number = value == number,
    operator == OPR_NEQ ? number = value != number,
    operator == OPR_LND ? number = value && number,
    operator == OPR_LOR ? number = value || number,
    operator == OPR_NOT ? number = ~number,
    operator == OPR_LNO ? number = !number,
    operator == OPR_SHL ? number = value << number,
    operator == OPR_SHR ? number = value >> number,
    operator == OPR_MOD ? number = value % number,
    {
        error(11)
        rval = 0
    }
    rval
}

constant_expression() :=
{
    stkval[7] := ?        ; Seven precedence levels
    stkopr[7] := ?
    stack := 0
    rval := 1

    token == OPERATOR || token == UNARY_OPERATOR ?
    {
        operator == OPR_ADR || operator == OPR_DRF ?
            rval = 0, stack > 5 ?
        {
            error(12)
            rval = 0
        },
        {
            stkopr[stack] = operator
            stkval[stack] = 0
            stack = stack + 1
            read_token()
        }
    }

    p := $
    rval ?
    {
        token == OPEN_PARENTHESIS ?
        {
            read_token()
            constant_expression() ?
            {
                token == CLOSE_PARENTHESIS ?
                    read_token(), rval = 0
            }, rval = 0
        },
        token == NUMBER || token == CHARACTER ?
                read_token(), rval = 0

        rval && ((token == OPERATOR) ||
                 (token == BINARY_OPERATOR)) ?
        {
            operator == OPR_SET ? rval = 0,
            {
                p := $

                stack > 0 && precedence(operator) <=
                    precedence(stkopr[stack - 1]) ?
                {
                    stack = stack - 1
                    evaluate(stkval[stack],stkopr[stack])
                    $ = p
                }
                stack > 5 ?
                {
                    error(12)
                    rval = 0
                },
                {
                    stkopr[stack] = operator
                    stkval[stack] = number
                    stack = stack + 1
                    read_token()
                }
            }
            $ = p
        }
    }

    rval ?
    {
        p = $
        stack > 0 ?
        {
            stack = stack - 1
            evaluate(stkval[stack], stkopr[stack])
        }
    }
    rval
}

compound_expression() :=
{
    token == OPEN_BRACE ?
    {
        read_token()
        ; Add new namespace
        oldbase := basespace
        newspace(0) ?
        {
            p := $
            token != CLOSE_BRACE ?
            {
                @primary_expression() ? $ = p
            },
            {
                read_token()
                oldbase != basespace ?
                {
                    namespace > 3 ?
                    {
                        d := oldbase - basespace
                        d < 0x80 || d >= 0xFF80 ?
                        {
                            writecode("\x83\xC4", 2)
                            writecode(#d, 1)
                        },
                        {
                            writecode("\x81\xC4", 2)
                            writecode(#d, 2);
                        }
                        ; 0100 83C400      ADD   SP,+00
                        ; 0103 81C48000    ADD   SP,0080
                    }
                    basespace = oldbase
                }
                oldspace(0)
            }
        }, 0
    }
}

_primary_expression() :=
{
    pos[3] := ?
    r := 0

    read_position(#pos)

    constant_expression() ?
    {
        function ?
        {
            ; Assignment
            writecode("\x8B", 1)
            writecode(#number, 2)
            ; 0100 B80000          MOV     AX,0000
        },
        {

            ; Add constant to heap
            writeheap(#number, 2)

        }
        r = 1
    },
    {
        set_position(#pos)
        token == OPEN_BRACE ? r = compound_expression(),
        {
            read_position(#pos)
            ; Here we have an ambiguity. If we read a
            ; symbol, we may have a declarator; we need
            ; to look for an ':', or we need to look
            ; for an '[ constant_expression ] :='
            ; sequence to determine what we have here.

            token == SYMBOL ?
            {
                read_token()
                token == OPEN_BRACKET ?
                {
                    read_token()
                    constant_expression() &&
                        token == CLOSE_BRACKET ?
                            read_token(), token = 0

                }
                token == ASSIGN_OPERATOR ?
                {
                    set_position(#pos)
                    r = @definition()
                },
                {
                    set_position(#pos)
                    r = simple_expression()
                }
            }, r = simple_expression()
        }
    }

    (r ? (token == QUESTION_MARK)) ?
    {
        f[2] := 0, 0
        a := ?
        writecode("\x09\xC0\x75\x03\xE9\x00\x00", 7)
        ; 0100 09C0            OR      AX,AX
        ; 0102 7503            JNZ     0107
        ; 0104 E90000          JMP     0107

        seek(com, #f, 1)
        f[0] < 2 ? f[1] = f[1] - 1
        f[0] = f[0] - 2
        a = address
        read_token()

        @primary_expression() ?
        {
            g[2] := 0, 0
            h[2] := 0, 0

            token == COMMA ?
            {
                writecode("\xE9\x00\x00", 3)
                ; 0100 E90000          JMP     0103
                seek(com, #h, 1)
                h[0] < 2 ? h[1] = h[1] - 1
                h[0] = h[0] - 2
            }

            seek(com, #g, 1)
            seek(com, #f, 0)
            a = address - a
            write(com, #a, 2)
            seek(com, #g, 0)
            a = address

            token == COMMA ?
            {
                read_token()
                r = @primary_expression()
            }

            h[0] || h[1] ?
            {
                g[0] = (g[1] = 0)
                seek(com, #g, 1)
                seek(com, #h, 0)
                a = address - a
                write(com, #a, 2)
                seek(com, #g, 0)
            }
        }, r = 0
    }
    r
}

declarator() :=
{
    token == SYMBOL ?
    {
        read_token()
        t := token
        t == OPEN_PARENTHESIS ?
        {
            function ? error(13),
            {
                addname(#symbol, address)

                ; Function preamble emitted here
                writecode("\x55\x89\xE5", 3)
                ; 0100 55              PUSH    BP
                ; 0101 89E5            MOV     BP,SP

                function = 1
                ; start new local namespace
                newspace(1)
                basespace = 0
                read_token()
                p := $
                token == SYMBOL ?
                {
                    addname(#symbol, basespace)
                    basespace = basespace - 2
                    read_token()
                    token == COMMA ?
                    {
                        read_token()
                        $ = p
                    }
                }
                {
                    ; Fix up newly added symbols
                    i := 0
                    basespace = 2 - basespace
                    p := $
                    i < basespace ?
                    {
                        space[currspace + i + 1] =
                                space[currspace + i + 1] +
                                    basespace
                        i = i + 2
                        $ = p
                    }
                }
                basespace = 0
                token == CLOSE_PARENTHESIS ?
                {
                    read_token()
                }, error(14)
            }
        },
        t == OPEN_BRACKET ?
        {
            read_token()
            constant_expression() ?
            {
                number = number * 2
                function ?
                {
                    basespace = basespace - number

                    number < 0x80 || number >= 0xFF80 ?
                    {
                        number = number & 0xFF
                        writecode("\x83\xEC", 2)
                        writecode(#number, 1)
                    },
                    {
                        writecode("\x81\xEC", 2)
                        writecode(#number, 2)
                    }
                    ; 0100 83EC02          SUB     SP,+02
                    ; 0103 81EC8000        SUB     SP,0080
                    addname(#symbol, basespace)
                },
                {
                    basespace = basespace + number
                    symbol[0] = symbol[0] | 0x80
                    addname(#symbol, heapadr + 1)
                }
                token == CLOSE_BRACKET ?
                {
                    read_token()
                    1
                }, 0
            }, error(15)
        },
        {

            ; add symbol to current namespace
            function ?
            {
                basespace = basespace - 2
                writecode("\x83\xEC\x02", 3)
                addname(#symbol, basespace)
                ; 0100 83EC02          SUB     SP,+02
            },
            {

                ; High bit0 indicates a heap symbol
                symbol[0] = symbol[0] | 0x80
                addname(#symbol, heapadr + 1)
            }
            1
        }
    }, 0
}

initializer() :=
{
    ; Whatever we do, at this point our lvalue is the
    ; last item in our current namespace.

    a := space[currspace + 1]
    rval := 1
    p := $

    token == QUESTION_MARK ?
    {
        ; We're happy. No code emitted.
        function == 0 ? writeheap("\x00\x00", 2)
        read_token();
    },
    @primary_expression() ?
    {
        (namespace == 2 ? function) ?
        {
            ; Function postamble emitted here
            writecode("\x89\xEC\x5D\xC3", 4)
            ; 0100 89EC            MOV     SP,BP
            ; 0102 5D              POP     BP
            ; 0103 C3              RET

            function = 0
            oldspace(1)
        },
        {
            function ?
            {
                ; Emit assignment code for local
                ; variable. Fixed-length code needed to
                ; ensure $ works properly.
                writecode("\x89\x86", 2)
                writecode(#a, 2)
                ; 010D 89868000        MOV   [BP+0080],AX
                a = a + 2
            }
        }
    }, rval = 0

    rval ?
    {
        token == COMMA ?
        {
            read_token()
            $ = p
        },
        {
            p = $
            heapadj > heapadr ?
            {
                writeheap("\x00\x00", 2);
                $ = p
            }
            1
        }
    }
}

_definition() :=
{
    declarator() ?
    {
        token == ASSIGN_OPERATOR ?
        {
            p := $
            read_token()
            initializer()
        }, 0
    }, 0
}

program() :=
{
    newspace(0)

    ; Startup code
    writecode("\xBF\x10\x01\xBB\x81\x00\x02\x1E\x80\x00\
xB8\x82\x00\x88\x27\x80\xFB\x81\x75\x02\x88\xD8\x50\xE8\x
05\x00\x83\xC4\x02\xCD\x20\xC3", 32)

    ; 0100 BF1001    MOV     DI,0110   ; Heap base at
                                      ; offset 1
    ; 0103 BB8100    MOV     BX,0081   ; Command line
    ; 0106 021E8000  ADD     BL,[0080]
    ; 010A B88200    MOV     AX,0082
    ; 010D 8827      MOV     [BX],AH
    ; 010F 80FB81    CMP     BL,81
    ; 0112 7502      JNZ     0116
    ; 0114 88D8      MOV     AL,BL
    ; 0116 50        PUSH    AX        ; as function
                                      ; parameter
    ; 0117 E80500    CALL    011F      ; start address at
                                      ; offset 24
    ; 011A 83C402    ADD     SP,+02    ; must be relative
                                      ; to 0x11A
    ; 011D CD20      INT     20
    ; 011F C3        RET

    read_token()
    p := $
    token != FILE_END ?
    {
        @definition() ? $ = p, error(16)
    }

    c[2] := 1, 0
    seek(com, #c, 0)
    write(com, #address, 2)

    a := findname("_\0", 1)
    a ?
    {
        a = a - 0x011A
        c[0] = 24
        c[1] = 0
        seek(com, #c, 0)
        write(com, #a, 2)
    }, error(0)
    0
}

_(arg) :=
{
    definition = #_definition
    primary_expression = #_primary_expression

    c[128] := ?

    n := strlen(arg)
    strcpy(#c, arg)

    at(#c, n - 2) != '.' || at(#c, n - 1) & 0xDF != 'W' ?
        strcpy(#c + n, ".W\0"), n = n - 2

    src = open(#c, 0);
    strcpy(#c + n, ".COM\0");
    com = open(#c, 1)
    strcpy(#c + n, ".TMP\0");
    tmp = open(#c, 1)

    src == 0 ?
        puts(stderr, "Can't open source file\r\n\0"),
    tmp == 0 ?
        puts(stderr, "Can't open temporary file\r\n\0"),
    com == 0 ?
        puts(stderr, "Can't open output file\r\n\0"),
    {
        program()
        close(src)
        close(tmp)
        tmp = open(#c, 0)
        tmp ?
        {
            b[512] := ?
            n := read(tmp, #b, 512)
            p[2] := 0, 0
            seek(com, #p, 2)
            p = $
            n > 0 ?
            {
                write(com, #b, n)
                n = read(tmp, #b, 512)
                $ = p
            }
            close(tmp)
        }
        unlink(#c)
        close(com)

        puts(stdout, "\r\nAddress map (global
symbols)\r\n==========================\r\n\0");
        n = space[16382]
        n == 0 ? n = currspace
        p := $
        n < 16379 ?
        {
            s := #space + space[n + 2] << 1
            h := @s[0] & 0x80
            @s[0] = @s[0] & 0xFF7F

            printf(s, (h?"heap\0","code\0"), space[n+1] +
                (h?address-1,0), "%x (%s) %s\r\n\0", stdout)

            n = n + 2
            $ = p
        }
    }
}
```